



Product name	:	MoTip Tuning Line Backlight
Colour	:	Black Red
Article number	:	00260 00261
Supplier / Producer	:	MOTIP DUPLI B.V. Wolframweg 2 NL-8471 XC WOLVEGA Telephone number +31 561 – 69 44 00 Telefax number +31 561 – 69 44 31

Product description

High quality transparent lacquer to highlight backlights.

Product characteristics

Lasting gloss
Scratch free and shock proof
Resistant to petrol, chemicals and weather influences
Good adhesion
Not suitable to treat surfaces of polycarbonate

Physical and Chemical Characteristics

Contents	:	400 ml
Basis	:	Alkyd resin
VOC content	:	Approximately 90% w/w
Solid content	:	Approximately 10% w/w
Gloss	:	High gloss 90 at an angle of 60°
Coverage	:	Approximately 8 backlights
Dust dry	:	After 30 minutes
Tack free	:	After 2 hours
Hardened/Re-sprayable	:	After 4 hours

Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface must be clean, dry and free of grease.

Treatment

Aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Spray the lacquer in several thin layers, till the desired result has been achieved. (Before applying the next layer, again shake the aerosol).

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.